


BD - 05T Series - Micro Diaphragm Pump

Model:BD-05T0610ACM

Performance Data	
Model(for Standard)	BD-05T0610ACM
Voltage Range	200~220V
Maximum Flow	6L/min
Max Negative Pressure	$\geq -70\text{KPa}$
Maximum Positive Pressure	1-1.5 Bar
Motor Data	
Motor Type	220vac/50Hz Shaded pole motor
Max power	50W
Waterproof Lever	IP00
Physical Properties	
Storage temperature	$-40^{\circ}\text{C}\sim 60^{\circ}\text{C}$
Operating environment	$-20^{\circ}\text{C}\sim 50^{\circ}\text{C}$
Max Medium temperature	200°C
Material	
Head of pump	Stainless Steel 316
Diaphragm	Imported PTFE
Valves	EPDM(Customized FKM)
Pump body	Aluminum alloy
Dimension	122*62*122mm
Weight	1.6kg




Features

Optimized pump body to by dynamic balance to provide a large flow rate while maintaining a relatively low vibration.

- Small volume and low noise
- Long life and high-quality performance
- High performance hood pole motor, imported ball bearing to ensure >8000 hours lifetime
- Provide high quality PTFE material, withstand a variety of gas corrosion resistance
- Professional seal design ensures low leakage rate.
- High quality imported PTFE diaphragm, withstand a variety of gas corrosion

Drawing(mm)



Curve

